

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

10/527563

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/025240 A2

(51) International Patent Classification⁷: G01M 3/00

(21) International Application Number:
PCT/DK2003/000589

(22) International Filing Date:
11 September 2003 (11.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2002 01335 11 September 2002 (11.09.2002) DK

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): BACTO-FORCE A/C [DK/DK]; 45, Amaliegade, DK-8600 Silkeborg (DK).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): PEDERSEN, Elgil, Appel [DK/DK]; 43, Hvinnindalvej, DK-8600 Silkeborg (DK).

(74) Agent: CHAS. HUDE A/S; 33 H.C. Andersens Boulevard, DK-1780 Copenhagen V (DK).

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A METHOD OF DETECTING LEAKAGE IN A HEAT EXCHANGER

(57) Abstract: A method is provided for detecting leakage in a heat exchanger by circulating a tracer under pressure from the first side of said heat exchanger to the second side and then from the second side to the first side subsequent to reversing the direction of the pressure. In order to prevent a false test result it has previously been necessary to make sure that all tracers, for example electrolytes, colorants, or fluorofors, were rinsed from the first side prior to circulating the tracers from the second side to the first side. This time consuming and at the same time unreliable rinsing process is avoided by the method of the present invention by adding a second tracer from the second side.



WO 2004/025240 A2

Title: A method of detecting leakage in a heat exchanger

Technical Field

- 5 The present invention relates to a method according to the preamble of claim 1.

Background Art

10 It is known to detect leakage in a heat exchanger by subjecting the first or the second side of said heat exchanger to pressure followed by a measuring of whether a loss of pressure occurs. However, this method is not reliable as the heat exchanger may have such a small hole that it can maintain the pressure for such a long period of time that it creates a false sense of security.

15 It is also known under pressure to circulate a liquid admixed an electrolyte on the first side of the heat exchanger, referred to as the donor face, and without pressure to circulate a second liquid on the second side of said heat exchanger, referred to as the recipient face. During the test, it is measured whether the conductance increases on the recipient face as a result of a leakage of donor liquid with electrolyte into the re-
20 cipient liquid.

It is also known to use the same principle as described above, where the tracer is a colorant or a fluorescent substance, referred to as a fluorofor, instead of being an electrolyte.

25

The plates in a heat exchanger are pressed into a wave pattern so as both to enlarge the surface of the plates and to cause a turbulence in the liquid flow passing through the heat exchanger. Due to the wavy pattern of the plates, said plates rest on each other in the assembled state of the heat exchanger.

30

When the donor face is subjected to pressure, which results in a differential pressure, the crests of the wavy patterns are pressed against each other. As a result, a possible leakage located at the crest of the wave pattern is not detected as the compression of the plates presses said plates upwards against each other, thereby closing the leakage, which is not detected accordingly.

In order to solve this problem, many have chosen to pressure test the heat exchanger from both sides. However, such a solution causes a problem when tracers are used. It is necessary to make sure that such tracers, for example electrolytes, colorants or fluorofors, are rinsed completely from the original donor face to prevent a false reaction and consequently a false test result.

Disclosure of Invention

The object of the present invention is to provide a method of the type mentioned above so as to avoid the laborious rinsing of tracers which also causes unreliable measuring results.

The object of the invention is obtained by a further development of the method of the type mentioned above and as stated in the characterising part of claim 1.

When the first tracer according to the preamble of claim 1 is detectable on the recipient face, then the test is completed, per se, with the detection of a leakage.

When the first tracer according to the preamble of claim 1 is not detectable on the recipient face, the heat exchanger can be pressure tested from the side which was previously the recipient face without necessitating a rinsing out of the first tracer. As a result, it is only necessary to measure whether the second tracer is detectable on the new recipient face. i.e. the original donor face.

Claim 2 deals with examples of possible tracers. It is merely important that the tracer used at the pressure test of the heat exchanger from the second side differs from the tracer used at the pressure test of the heat exchanger from the first side.

Claims

1. A method of detecting leakage in a heat exchanger, particularly a plate heat exchanger, by circulating under pressure a liquid admixed a first tracer on one first
5 side of said heat exchanger, referred to as the donor face, and by circulating a second liquid under no pressure or under a lower pressure on the second side of said heat exchanger, referred to as the recipient face, and by measuring whether said first tracer is detectable on said recipient face, **characterised in that** a second tracer is added to the second liquid on the second side of the heat exchanger in case the first
10 tracer was undetectable on the recipient face, whereafter the pressure is reversed in such a manner that said recipient face is the new donor face and the first donor face is the new recipient face, and that it is measured whether said second tracer is detectable on said new recipient face.
- 15 2. A method according to claim 1, **characterised in that** the first tracer is in form of an electrolyte, one of two different colorants or one or two different fluorescent substances, and the second tracer is in form of one of the former five tracers differing from the first tracer.

(12) INTERNATIONAL PUBLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/527563



(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/025240 A3

(51) International Patent Classification⁷: G01M 3/20, 3/22

(21) International Application Number:
PCT/DK2003/000589

(22) International Filing Date:
11 September 2003 (11.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2002 01335 11 September 2002 (11.09.2002) DK

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(71) Applicant (*for all designated States except US*): BACTO-FORCE A/C [DK/DK]; 45, Amaliegade, DK-8600 Silkeborg (DK).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): PEDERSEN, Eigil, Appel [DK/DK]; 43, Hvinnindalvej, DK-8600 Silkeborg (DK).

(74) Agent: CHAS. HUDE A/S; 33 H.C. Andersens Boulevard, DK-1780 Copenhagen V (DK).

(88) Date of publication of the international search report:
13 January 2005

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A METHOD OF DETECTING LEAKAGE IN A HEAT EXCHANGER

(57) Abstract: A method is provided for detecting leakage in a heat exchanger by circulating a tracer under pressure from the first side of said heat exchanger to the second side and then from the second side to the first side subsequent to reversing the direction of the pressure. In order to prevent a false test result it has previously been necessary to make sure that all tracers, for example electrolytes, colorants, or fluorofors, were rinsed from the first side prior to circulating the tracers from the second side to the first side. This time consuming and at the same time unreliable rinsing process is avoided by the method of the present invention by adding a second tracer from the second side.



WO 2004/025240 A3

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 03/00589

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G01M3/20 G01M3/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G01M G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)
EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 416 323 A (HOOTS JOHN E ET AL) 16 May 1995 (1995-05-16) column 8, line 5 - line 10 column 13, line 10 - line 22 ---	1,2
Y	WO 86 03836 A (SVERIGES GEOL AB) 3 July 1986 (1986-07-03) page 2, line 35 -page 3, line 2 abstract ---	1,2
Y	US 5 759 857 A (RENNER TERENCE A ET AL) 2 June 1998 (1998-06-02) claims 1,2 ---	1,2
Y	WO 01 42756 A (ACCUSENSE SYSTEMS LTD ;WERNER THOMAS (GB)) 14 June 2001 (2001-06-14) abstract ---	1,2
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

16 November 2004

Date of mailing of the international search report

01.12.04

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

HENRIK ERIKSSON/LR

INTERNATIONAL SEARCH REPORT

International Application No

PCT/K 03/00589

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,A	WO 02 086438 A (TETRA LAVAL HOLDINGS & FINANCE ;RABELLE GERARD (FR)) 31 October 2002 (2002-10-31) abstract -----	1,2

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PATENT NO 03/00589

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5416323	A	16-05-1995	US 5304800 A	19-04-1994
			AT 166719 T	15-06-1998
			BR 9304674 A	01-11-1994
			CA 2102338 A1	11-05-1994
			DE 69318803 D1	02-07-1998
			DE 69318803 T2	22-10-1998
			DK 597659 T3	25-01-1999
			EP 0597659 A2	18-05-1994
			ES 2118908 T3	01-10-1998
			JP 6281528 A	07-10-1994
			KR 247667 B1	01-04-2000
			MX 9306984 A1	31-01-1995

WO 8603836	A	03-07-1986	SE 446033 B	04-08-1986
			AT 80456 T	15-09-1992
			DE 3586631 D1	15-10-1992
			DE 3586631 T2	08-04-1993
			DK 388586 A	15-08-1986
			EP 0242363 A1	28-10-1987
			FI 872708 A ,B,	17-06-1987
			NO 863199 A ,B,	08-08-1986
			SE 8406449 A	19-06-1986
			WO 8603836 A1	03-07-1986

US 5759857	A	02-06-1998	NONE	

WO 0142756	A	14-06-2001	AU 2194701 A	18-06-2001
			EP 1236028 A1	04-09-2002
			WO 0142756 A1	14-06-2001
			US 2003056572 A1	27-03-2003

WO 02086438	A	31-10-2002	FR 2823847 A1	25-10-2002
			BR 0209075 A	10-08-2004
			EP 1390706 A1	25-02-2004
			WO 02086438 A1	31-10-2002
			US 2004129061 A1	08-07-2004
